

Quality Guarantee

Conservation board 012 ES – chamois/natural white, multiple ply (thicknesses: 0.6/1.8 mm)



We hereby confirm that our "Conservation board 012 ES – chamois/natural white, multiple ply (thicknesses: 0.6/1.8 mm)" fulfils the following characteristics:

Board

- 100% bleached cellulose
- without the usage of recycling fibres
- free of wooden fibres
- Kappa level 1 – 2 = lignin-free
- pH 7.5 - 10.0 = acid-free (in accordance with ISO 6588-1:2020)
- alkaline buffer > 3% natural calcium carbonate (GCC)
- sizing: neutral/synthetic (without alum additive)
- without optical brightening agents
- special surface strengthening (dirt-resistant and erasable)
- Photographic Activity Test (PAT) passed in accordance with ISO 18916:2007

Glue used for lamination

- emission-free starch-based adhesive (based on potato starch)
- VOCs-free
- free of solvents and softening agents
- pH approx. 7.0
- ageing-resistant (permanent)
- Photographic Activity Test (PAT) passed in accordance with ISO 18916:2007

This quality corresponds to the technological basis of the following standards:

DIN EN ISO 9706	Information and documentation – Paper for documents – Requirements for permanence
ANSI/ NISO Z.39.48	American National Standard for Permanence of Paper for Publications and Documents in Libraries and Archives
DIN 6738:2007	Highest level of permanency LDK 24-85

*We guarantee legally-binding that the above stated material meets the listed characteristics.
The material is ageing-resistant and provides active protection for the artefact.*

KLUG-CONSERVATION September 2023

Peter Langhammer
Quality Assurance