

## Quality Guarantee

Corrugated board – EB 5.0 mm - 1160 gsm



We hereby confirm that our "Corrugated board – EB 5.0 mm - 1160 gsm" fulfils the following characteristics:

### Base paper

- 100% bleached cellulose
- without the usage of recycling fibres
- free of wooden fibres
- weight 1160 gsm
- Kappa level 1 – 2 = lignin-free
- pH 7.5 - 10.0 = acid-free (in accordance with ISO 6588-1:2020)
- alkaline buffer > 2% natural calcium carbonate (GCC)
- sizing: neutral/synthetic (without alum additive)
- top surface sizing: Cobb<sub>60</sub> in accordance with ISO 535 < 25
- without optical brightening agents
- light-fastness approx. 7 – 8 (= extremely good) in accordance with the wool scale (EN ISO 105-B02)
- no bleeding in accordance with DIN ISO 16245:2012
- Photographic Activity Test (PAT) passed in accordance with ISO 18916:2007

### Glue used for the corrugated board

- starch-based adhesive
- pH > 8.0

This quality corresponds to the technological basis of the following standards:

|                        |                                                                                                                                                        |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| DIN EN ISO 9706        | Information and documentation – Paper for documents – Requirements for permanence                                                                      |
| DIN ISO 16245 - type A | Information and documentation – Boxes, file covers and other enclosures, made from cellulosic materials, for storage of paper and parchment documents. |
| NF Z 40-014            | Requirements and criteria for selecting paper and cardboard for conserving paper and parchment documents                                               |
| ANSI/ NISO Z.39.48     | American National Standard for Permanence of Paper for Publications and Documents in Libraries and Archives                                            |
| DIN 6738:2007          | Highest level of permanency LDK 24-85                                                                                                                  |

*We guarantee legally-binding that the above stated material meets the listed characteristics.  
The material is ageing-resistant and provides active protection for the artefact.*

KLUG-CONSERVATION May 2024

Peter Langhammer  
Quality Assurance

