

Technical data sheet

Mounting board 018 - white, single ply (thickness: 0.5 mm)



Specifications: An economically priced, white solid colour (dyed throughout) mounting board

with excellent diagonal cutting characteristics. Ideal for conservation-quality

picture framing and mounting, displays and museum exhibits.

Sizes ex-stock: $100 \times 140 \text{ cm}$

Material characteristics: Board

• 100% bleached cellulose

without the usage of recycling fibres

free of wooden fibres

• Kappa level < 5 = lignin-free

• pH 7.5 - 10.0 = acid-free (in accordance with ISO 6588-1:2020)

alkaline buffer > 3% natural calcium carbonate (GCC)

• sizing: neutral/synthetic (without alum additive)

 Photographic Activity Test (PAT) passed in accordance with ISO 18916:2007

This quality corresponds to the technological basis of the following standards:

DIN EN ISO 9706 Information and documentation – Paper for documents – Requirements for

permanence

ANSI/ NISO Z.39.48 American National Standard for Permanence of Paper for Publications and

Documents in Libraries and Archives

DIN 6738:2007 Highest level of permanency LDK 24-85

Further information, such as our Quality Guarantee, certificates of independent testing institutions and information regarding application methods and instructions are stated on our website klug-conservation.com.