

## Technical data sheet

Cardboard pages 240 and 330 gsm



### Specifications:

Cardboard pages with 2-hole or 4-hole perforation (according to ISO standard). Suitable as covers/dividers for A4-files or for mounting purposes. Made from archival board 048 light grey, either 240 or 330 gsm, surface-refined, dirt-resistant, erasable and rub-proof (resistant to dry wiping).

### Material characteristics:

- 100% bleached cellulose
- without the usage of recycling fibres
- free of wooden fibres
- Kappa level 1 – 2 = lignin-free
- pH 7.5 - 10.0 = acid-free (in accordance with ISO 6588-1:2012)
- alkaline buffer > 3% natural calcium carbonate (GCC)
- sizing: neutral/synthetic (without alum additive)
- sizing according to Cobb<sub>60</sub> < 25
- without optical brightening agents
- light-fastness 5 – 6 (good – very good) in accordance with the wool scale (ISO 105- B02)
- special surface strengthening (dirt-resistant and erasable)
- no bleeding in accordance with DIN ISO 16245:2012
- Photographic Activity Test (PAT) passed in accordance with ISO 18916:2007

Further information, such as our Quality Guarantee, certificates of independent testing institutions and information regarding application methods and instructions are stated on our website [klug-conservation.com](http://klug-conservation.com).